

Perspiration/Spray



DL-2012



DL-3012



ISO QUALITY SYSTEM CERTIFICATION

Feature

- Consists of stainless steel and acrylic material.
- Applies to all kinds of textile fabrics on color fastness to perspiration.
- Keeps the loading pressure with spring pressure rack during specimen drying.
- Standard : KSK 0715, ISO 105-E01/02/03/04, AATCC 15, JIS L 0847, JIS L 0848

Feature

- Consists of stainless steel material exclusive of a funnel.
- Easy to remove the specimen.
- Consistent water flow by the precise spray nozzle.
- Standard : KSK 0590, ISO 4920, AATCC 22

ACCESSORIES



Weight



Plastic plate



Funnel



Nozzle



150mm Scale



Clamp

Specification

Model	DL-2012
Specimen size	115 x 63mm
Load	4.5kg (Standard) - AATCC 5kg (Option) - ISO
Plastic plate	21ea
Material	SUS#304 polishing
Weight (Approx.)	7kg (±0.5kg)
Dimension (Approx.)	200(W) x 76(D) x 150(H)mm

Specification

Model	DL-3012
Specimen size	200 x 200mm
Test angle	45°
Spray nozzle	0.9mm dia. 19 holes
Specimen hold	150mm dia.
Funnel diameter	150mm dia. (500ml)
Weight (Approx.)	5kg (±0.5kg)
Dimension (Approx.)	250(W) x 350(D) x 500(H)mm